

NEW Optimas T22 Paver Laying Machine



T22 concentrates on the essential. Due to the design, T22 ensures a brilliant price-performance ratio! Solid, maintenance-friendly, and easy operation are the remarkable attributes!

Dimensions and weight:

Height 2000 mm, Width 1200 mm, Length 3700 mm (without clamp) / 4000 mm (with clamp)
Weight 1100 kg.

BASIC Features:

- Paver-Grab "Multi6" incl. tap down device
- Diesel engine, 3 cylinders, water-cooled with electrical ventilation, 18,9 kW (25,7 hp)
- Hydraulic rotator head 300°
- Half automatic
- Hydrostatic drive
- Powder coated color
- 3 working lights (2 in front 1 rear)
- Warning light
- Seat with arm rest
- Adjustable steering column
- Adjustable pedal
- Hand grip operation /Joystick
- Hour counter
- Resettable work cycle counter
- Horn



COMFORT features:

- Cabin
- Heating
- Radio

Paver Clamp - All gripper systems from one source

We will give you competent advice in regard to which system is best-suited for your individual requirements. The available options are:

- Optimas Paver Clamp **Multi6**
- Optimas Paver Clamp **Easy1** (6 gripper arms with 6 cylinders) or (2 gripper arms with 1 cylinder)



Technical data:

Height: 2.000 mm
Length: 3.700 mm without Paver-Grab, 4.000mm with Paver-Grab
Width: 1.200 mm
Weight: 1.100 kg

Further Data:

Diesel engine, 3 cylinders, water-cooled with electrical ventilation, 18,9 kW (25,7 hp), noise-insulated, hydrostatic traction drive with one-pedal steering control, fully hydraulic four-wheel turntable/articulated steering, rear suspension with independent pendulum wheel suspension, hydrostatic locking brake; tank capacity 24 litres diesel, coating according to RAL 2004 powder-coated, CE-certified

Contact us!

PATHFINDER

695 Ottawa Beach Rd, Holland MI 49424
www.PathfinderSystem.com | (616)395-8447